



About The Product

Polypropylene Random (PPR) pipes and fittings are most reliable in plumbing and water supply pipelines inside the building, due to their chemical features and fusion welding, which ensures the plumber has a perfect seal tight system. The PPR type 3 used in the production of JET PLAST PPR system has a high molecular weight and excellent creep resistance fundamental characteristics for the transportation of hot fluids under pressure. It also has good resilience which ensures ease of installation even with temperatures under 0°C. JET PLAST pipes are made of 100% virgin material which guarantees they last long; durable and no deposits seen.

PPRC Pipes

PPRC Pipes



PN-16 SDR 7.4				PN-20 SDR 6			
SR#	D(mm)	Wall Thickness (mm)	Pack	SR#	D(mm)	Wall Thickness (mm)	Pack
1	20	2.8	30	1	20	3.4	30
2	25	3.5	25	2	25	4.2	25
3	32	4.4	20	3	32	5.4	20
4	40	5.5	15	4	40	6.7	15
5	50	6.9	10	5	50	8.3	10
6	63	8.6	5	6	63	10.5	5
7	75	10.3	5	7	75	12.5	5
8	90	12.3	3	8	90	15.0	3
9	110	15.1	2	9	110	18.3	2

PPRC Fittings

90 Tee with Female Threaded offtake



Sr#	D(mm)	F(BSP)	Pack
1	25	G 1/2 (f)	100
2	25	G 3/4 (f)	100
3	32	G 1/2 (f)	45
4	32	G 3/4 (f)	45
5	32	G 1 (f)	45

90 Tee



Sr#	D(mm)	Pack
1	25	100
2	32	60
3	40	40

90 Reducing Tee



Sr#	D(mm)	D(mm)	Pack
1	32	25	75
2	40	25	40
3	40	32	40
4	50	40	25

Socket



Sr#	D(mm)	Pack
1	25	200
2	32	175
3	40	75
4	50	45
5	63	30

PPRC Fittings

Reducing Socket



Sr#	D(mm)	D(mm)	Pack
1	25	32	150
2	25	40	100
3	32	40	100

Socket with female threaded offtake



Sr#	D(mm)	F(BSP)	Pack
1	25	G ½ (f)	200
2	25	G ¾ (f)	150
3	32	G ½ (f)	150
4	32	G ¾ (f)	150
5	32	G 1 (f)	60
6	40	G 1-¼(f)	40

Socket with male threaded offtake



Sr#	D(mm)	F(BSP)	Pack
1	25	G ½ (m)	200
2	25	G ¾ (m)	100
3	32	G ½ (m)	
4	32	G ¾ (m)	
5	32	G 1 (m)	60
6	40	G 1-¼(m)	

90 Elbow with female threaded offtake



Sr#	D(mm)	F(BSP)	Pack
1	25	G ½ (f)	100
2	25	G ¾ (f)	100
3	32	G ½ (f)	75
4	32	G ¾ (f)	75
5	32	G 1 (f)	45
6	40	G 1-¼(f)	30

PPRC Fittings

90° Elbow with male threaded offtake



Sr#	D(mm)	F(BSP)	Pack
1	25	G ½ (m)	100

90° Reducing Elbow



Sr#	D(mm)	D(mm)	Pack
1	25	32	100
2	32	40	60

90° Elbow



Sr#	D(mm)	Pack
1	25	150
2	32	100
3	40	60

90° Elbow with Double female threaded offtake



Sr#	D(mm)	D(mm)	Pack
1	25	G ½ (f)	30

PPRC Fittings

Gate Valve



Sr#	D(mm)	Pack
1	25	30
2	32	20

Union



Sr#	D(mm)	Pack
1	25	75
2	32	50

Under Ground Valve



Sr#	D(mm)	Pack
1	25	75

Stop Cork



Sr#	D(mm)	Pack
1	25	40

End Cap



Sr#	D(mm)	Pack
1	25	400
2	32	200

Pipe Clamp



Sr#	D(mm)	Pack
1	25	600
2	32	400

Over Cross



Sr#	D(mm)	Pack
1	25	100
2	32	45

Plug with male threaded offtake



Sr#	D(mm)	F(BSP)	Pack
1	25	G 1/2 (m)	600